

Inhaltsverzeichnis

--

Referenz:ParserHooks

Um die Seitenabschnitte zu nummerieren, können Sie folgende Anweisungen an das Ende der Seite *MediaWiki:Common.css* kopieren:



Die Überschriftennummerierung über common.css wird nicht im PDF-Export übernommen.

```
article {counter-reset: h2counter;}
article h1 {counter-reset: h2counter;}
article h2 {counter-reset: h3counter;}
article #toc h2#mw-toc-heading {counter-reset: h2counter 0}
article h3 {counter-reset: h4counter;}
article h4 {counter-reset: h5counter;}
article h5 {counter-reset: h6counter;}
article h2:before, article #mw-content-text h2:before {
    content: counter(h2counter) ".\0000a0\0000a0";
    counter-increment: h2counter;
}
article #toc h2#mw-toc-heading:before {content:""}
article h3:before {
    content: counter(h2counter) "." counter(h3counter) ".\0000a0\0000a0";
    counter-increment: h3counter;
}
article h4:before {
    content: counter(h2counter) "." counter(h3counter) "." counter(h4counter) ".\0000a0\0000a0";
    counter-increment: h4counter;
}
article h5:before {
    content: counter(h2counter) "." counter(h3counter) "." counter(h4counter) "." counter(h5counter) ".\0000a0\0000a0";
    counter-increment: h5counter;
}
article h6:before {
    content: counter(h2counter) "." counter(h3counter) "." counter(h4counter) "." counter(h5counter) "." counter(h6counter) ".\0000a0\0000a0";
    counter-increment: h6counter;
}

/*Keine Nummerierung bei */
#mw-content-text .sectionflex h2::before, #mw-content-text .sectionflex h3::before,
#mw-content-text .bs-social-entity-wrapper h3::before {content:none}
#mw-content-text .mw-category h2::before, #mw-content-text .mw-category-generated h2::before,
#mw-content-text .mw-category h3::before, #mw-content-text .mw-category-generated h3::before {content:none}
.ns-special #mw-content-text h2::before, .ns-special #mw-content-text h3::before {content:none;}
#mw-content-text .bs-tag-pagetemplates h6::before {content:none}
```